



Variability in required ozone doses for removing pharmaceuticals from wastewater effluents

Antoniou, Maria; Hey, Gerly; Rodriguez Vega, Sergio; Spiliotopoulou, Aikaterini; Fick, Jerker; Tysklind, Mats; La Cour Jansen, Jes; Andersen, Henrik Rasmus

Published in:

13th International Conference on Environmental Science and Technology - Volume of Abstracts

Publication date:

2013

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Antoniou, M., Hey, G., Rodriguez Vega, S., Spiliotopoulou, A., Fick, J., Tysklind, M., La Cour Jansen, J., & Andersen, H. R. (2013). Variability in required ozone doses for removing pharmaceuticals from wastewater effluents. In T. D. Lekkas (Ed.), *13th International Conference on Environmental Science and Technology - Volume of Abstracts* (pp. 243). CEST.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

VARIABILITY IN REQUIRED OZONE DOSES FOR REMOVING PHARMACEUTICALS FROM WASTEWATER EFFLUENTS

MARIA G. ANTONIOU^{1,2}, GERLY HEY³, SERGIO RODRÍGUEZ VEGA⁴,
AIKATERINI SPILIOPOULOU¹, JERKER FICK⁵, MATS TYSKLIND⁵,
JES LA COUR JANSEN³ and HENRIK RASMUS ANDERSEN^{1,*}

¹ Department of Environmental Engineering, Technical University of Denmark, Miljøvej, Building 113, 2800 Kongens Lyngby, Denmark .

² Department of Environmental Science and Technology, Cyprus University of Technology, PO Box: 50329, 3603 Lemesos, Cyprus.

³ Water and Environmental Engineering at Department of Chemical Engineering, Lund University, P.O. Box 124, SE-221 00 Lund, Sweden.

⁴ Departamento de Ingeniería Química, Facultad de Ciencias Químicas, Universidad Complutense Madrid, 28040 Madrid, Spain.

⁵ Department of Chemistry, Umeå University, SE-90187 Umeå, Sweden.

*Corresponding authors e-mail: henrik@andersen.net

EXTENDED ABSTRACT

Aim of study. The aim of the present study was to investigate the ozone dosage required to remove active pharmaceutical ingredients (APIs) from biologically treated wastewater of varying quality originating from different wastewater treatment processes.

Methods. Secondary effluents from six Swedish wastewater treatment plants (WWTP) were spiked with 42 APIs (nominal concentration 1 µg/L) and treated with different O₃ doses (0.5-12.0 mg/L ozone) in bench-scale experiments¹. Concentrations of APIs were measured by SPE extraction using OASIS HLB cartridges followed by quantification using LC-MS-MS².

Results. For each wastewater effluent a profile of sensitivity of each API to a range of ozone doses were generated.

In order to obtain a parameter to compare the sensitivity of APIs to ozone in each wastewater the specific dose of ozone required to achieve one decade of removal of each investigated API (DDO₃) was determined for each effluent by fitting a first order equation to the remaining concentration of API at each applied ozone dose. Equation 1 describes the remaining API concentration in relation to its initial concentration after a specific O₃ dose is delivered (DO₃). The equation contains the O₃ dose required to remove 90% of the API as a constant (here noted as decadic dose of O₃ DDO₃). The fitted parameter is named the decadic dose of O₃, DDO₃.

$$(Eq.1) \quad \log\left(\frac{C}{C_0}\right) = \frac{-DO_3}{DDO_3} \Leftrightarrow C = C_0 \cdot 10^{\left(\frac{DO_3}{DDO_3}\right)}$$

Ozone dose requirements for APIs were found to vary significantly between wastewater effluents depending on their matrix characteristics.

The specific ozone dose was normalized to the dissolved organic carbon (DOC) of each effluent as shown in Table 1. The DDO₃/DOC ratios were comparable for each API between the effluents. 15 of the 42 investigated APIs could be classified as easily degradable (DDO₃/DOC ≤ 0.7), while 19 were moderately degradable (0.7 < DDO₃/DOC ≤ 1.4) and 8 were recalcitrant towards O₃-treatment (DDO₃/DOC > 1.4).

With this estimates of the required ozone dose required to remove any of the investigated APIs may be attained by multiplying the experimental average DDO₃/DOC obtained with the actual DOC of any effluent. The method predicts results which agrees with removal rates and ozone doses found in literature.


Variability in required ozone doses for removing pharmaceuticals from wastewater effluents

Henrik R. Andersen

3th International Conference on Environmental Science and Technology
(CEST2013)

6th September 2013, Athens

DTU Environment
Department of Environmental Engineering



Co-authors

**Maria G. Antoniou^{1,2}, Gerly Hey³, Sergio Rodríguez Vega⁴,
Aikaterini Spiliotopoulou¹, Jerker Fick⁵, Anna Ledin², Mats
Tysklind⁵, Jes la Cour Jansen³**

¹ Department of Environmental Engineering, Technical University of Denmark

² Department of Environmental Science and Technology, Cyprus University of Technology.

³ Water and Environmental Engineering at Department of Chemical Engineering, Lund, Sweden.

⁴ Departamento de Ingeniería Química, Facultad de Ciencias Químicas, Universidad Complutense Madrid, Spain.

⁵ Department of Chemistry, Umeå University, SE-90187 Umeå, Sweden.

**MistraPharma Project
of the Mistra Foundation, Sweden
funded part this research.**

Technical University of Denmark



LUND
UNIVERSITY



Objectives




- ❑ The overall objective of this study is to find a method to estimate the required ozone dose for removal of micropollutants - exemplified by active pharmaceutical ingredients (APIs) – in WWTP effluents of different quality.
- ❑ The specific objective of this study was to identify the required O_3 doses to achieve 90% degradation of selected different types of APIs.

Work done

- ❑ The removal of 42 APIs by different added ozone doses were investigated in effluents from 6 Swedish WWTP.
- ❑ A curve was fitted to the O₃ dose- API removal data in order to estimate the required O₃ doses to achieve 90% degradation of each pharmaceutical in each effluent.
- ❑ It was attempted to correlate the effective O₃ doses in different effluents with basic wastewater parameters (i.e., DOC, COD, alkalinity)
 - ❑ Rather than using the second order rate constants.
 - ❑ $k_{O_3,API} > 10^4 \text{ M}^{-1}\text{s}^{-1}$, easily degraded.
 - ❑ $k_{O_3,API} < 10^4 \text{ M}^{-1}\text{s}^{-1}$, are more recalcitrant to O₃
 - ❑ You cannot determine the O₃ doses needed (matrix effects)

Experiment and analysis

- 6 Effluents (secondary treatment) from WWTP (different treatment processes , matrix characteristic-COD, N-NH₄⁺, alkalinity) were spiked with an APIs mixture (45) of nominal concentration of 1 µg/L and treated by varying ozone doses in triplicate.
- Preparation of O₃ stock solution (~35mg/L O₃)
- Delivered O₃ dose (0,5 <O₃<12 mg/L) was measured with the indigo method ($\lambda=600\text{nm}$) in Milli-Q water.
- Bottles were placed in a waterbath at T=15°C
- Quantification of APIs - Liquid chromatography-tandem mass-spectrometry (LC-MS/MS)



A single parameter which describes the removal results by different ozone doses

- Our parameter, DDO_3 , is the O_3 dose required to achieve 90% removal of a micropollutant in an effluent.
- The concept was based on the equation suggested by James Bolton that correlates EED (electrical energy dose) of energy intensive treatment processes with the concentration reduction of the treatment target:




$$\log\left(\frac{C}{C_i}\right) = \frac{-1}{E_{EO}} EED$$

where C_i and C is the initial and the final concentration, respectively, EED is the electrical energy dose in kWh/m³ and E_{EO} is the electrical energy per order.

- This approach has been used before for the O_3 of estrogenic compounds from WW (Hansen et al., 2010):

$$\log\left(\frac{C}{C_o}\right) = -\frac{DO_3}{DDO_3} \Leftrightarrow C = C_o \cdot 10^{-\left(\frac{DO_3}{DDO_3}\right)}$$

Example of curve fitting to determine DDO_3



$$k_{O_3,API} = 2,62 \cdot 10^4 - 2,97 \cdot 10^5 \text{ (M}^1\text{s}^{-1}\text{)}$$

$$k_{HO\bullet,API} = 8,4 \cdot 10^9 \text{ (M}^1\text{s}^{-1}\text{)}$$

Benitez et al. *Chemosphere*, 2009, 77, 53-59.


Naproxen: a non-steroidal anti-inflammatory drug

Results: WW effluents characteristics







Table 1. Source and characterization of the wastewater effluents.

WWTP	Källby 1	Källby 2	Björnstorp	Öresundsverket	Sjölunda	Nykvarnsverket
	Eff1	Eff2	Eff3	Eff4	Eff5	Eff6
COD, mg/L	29	51	30	36	90	44
DOC, mg/L	7.5	6.5	5.2	8.1	13.7	8.4
Alkalinity, mg HCO ₃ ⁻ /L	244	154	185	229	256	164
pH	6.6	6.7	7.0	7.2	6.7	6.8
N-NH ₄ ⁺ , mg/L	1.36	2.98	0.77	4.93	1.86	5.98
SUVA, (L/mg)/m	2.74	2.94	2.07	2.10	1.86	2.01
A254, cm ⁻¹	0.206	0.190	0.107	0.171	0.256	0.168



Results: Required O₃ dose to degrade 45 pharmaceuticals in one effluent



Results: Required O₃ dose to degrade 45 pharmaceuticals in effluents from 6 sources




Results: Concentration profiles



- The intersect of the black horizontal line with the 10 % remaining API concentration (y-axis) indicates the corresponding DDO_3 . T-bar represent standard deviation with $n=3$.

Suggested enhanced ozone results treatment



API	DDO ₃ (ppm O ₃)						[DDO ₃ /DOC]						Ave
	Eff1	Eff2	Eff3	Eff4	Eff5	Eff6	Eff1	Eff2	Eff3	Eff4	Eff5	Eff6	
Easily degradable													
Repaglinide	2.6	3.7	1.8	4.1	8.7	1.5	0.35	0.57	0.35	0.50	0.64	0.18	0.43
Ezetimibe	3.2	4.6	1.5	3.8	8.0	2.0	0.43	0.71	0.29	0.47	0.58	0.24	0.45
Diltiazem	3.6	3.7	2.2	4.3	8.0	3.9	0.48	0.57	0.42	0.53	0.58	0.47	0.51
Eprosartan	3.2	4.9	1.9	4.5	9.1	4.2	0.43	0.76	0.37	0.55	0.66	0.50	0.55
Trimethoprim	4.0	4.3	2.1	4.4	9.7	3.9	0.53	0.67	0.40	0.54	0.71	0.47	0.55
Clomipramine	2.3	7.3	2.4	3.7	7.5	4.2	0.31	1.13	0.46	0.45	0.55	0.50	0.57
Risperidone	3.5	4.7	0.9	5.5	12.1	5.0	0.47	0.73	0.17	0.68	0.88	0.60	0.59
Hydroxyzine	3.4	5.7	1.9	4.8	10	4.8	0.45	0.88	0.37	0.59	0.73	0.57	0.60
Codeine	4.2	4.9	2.4	4.6	9.2	5.4	0.56	0.76	0.46	0.57	0.67	0.65	0.61
Carbamazepine	5.1	5.4	2.2	4.3	10.8	3.5	0.68	0.84	0.42	0.53	0.79	0.42	0.61
Naproxen	5.7	5.0	2.5	6.4	10	3.7	0.76	0.77	0.48	0.79	0.73	0.44	0.66
Fexofenadine	5.2	5.8	3.0	6.5	9.1	2.9	0.69	0.90	0.58	0.80	0.66	0.35	0.66
Orphenadrine	4.5	5.0	3.4	4.8	12.1	4.0	0.60	0.77	0.65	0.59	0.88	0.48	0.66
Diclofenac	4.7	5.8	NA*	3.5	10	NA*	0.63	0.90	NA*	0.43	0.73	NA*	0.67
Cilazapril	4.5	7.1	2.7	5.7	11	4.0	0.60	1.10	0.52	0.70	0.80	0.48	0.70
Moderately degradable													
Loperamide	2.0	4.5	<0.5	5.7	13.3	8.7	0.27	0.70	NA**	0.70	0.97	1.04	0.74
Glimepiride	7.0	7.6	3.6	6.7	>>8.9	0.6	0.93	1.18	0.69	0.82	NA**	0.07	0.74
Rosuvastatin	5.4	5.6	3.3	5	14.5	4.8	0.72	0.87	0.63	0.61	1.06	0.57	0.74
Haloperidole	4.8	7.8	1.5	6.3	11.8	5.9	0.64	1.21	0.29	0.77	0.86	0.71	0.75
Sulfamethoxazole	4.8	4.5	3.6	4.5	17.6	NA*	0.64	0.70	0.69	0.55	1.28	NA*	0.77
Verapamil	NA*	5.4	<0.5	5.0	10.5	7.5	NA*	0.84	NA**	0.61	0.77	0.90	0.78
Tramadole	5.7	5.8	3.4	6.3	13	6.4	0.76	0.90	0.65	0.77	0.95	0.77	0.80
Citalopram	5.0	7.8	2.0	7.1	15	5.0	0.67	1.21	0.38	0.87	1.09	0.60	0.80
Sertraline	6.4	5.2	1.7	7.9	12	11.6	0.85	0.81	0.33	0.97	0.88	1.39	0.87
Venlafaxine	5.3	6.3	3.4	6.4	16.6	9.3	0.71	0.98	0.65	0.79	1.21	1.11	0.91
Maprotiline	7.3	6.9	4.1	8.3	13.6	7.2	0.97	1.07	0.79	1.02	0.99	0.86	0.95
Bisoprolol	7.2	6.0	3.3	7.3	21	7.2	0.96	0.93	0.63	0.90	1.53	0.86	0.97
Amitriptyline	7.3	9.4	3.6	8.3	13.6	7.3	0.97	1.46	0.69	1.02	0.99	0.87	1.00
Metoprolol	6.9	6.9	3.8	7.4	18.2	8.8	0.92	1.07	0.73	0.91	1.33	1.05	1.00
Biperiden	5.9	6.3	4.3	7.3	23	7.4	0.78	0.98	0.83	0.90	1.68	0.88	1.01
Levonorgestrel	6.7	7.3	6.6	6.0	18.2	6.5	0.89	1.13	1.27	0.74	1.33	0.78	1.02
Fluoxetine	6.6	6.8	3.1	7.7	20	11.3	0.88	1.05	0.60	0.95	1.46	1.35	1.05
Irbesartan	8.7	7.7	5.4	11.5	13.7	4.3	1.16	1.19	1.04	1.41	1.00	0.51	1.05
Bupropion	8.1	8.0	5.2	9.3	>>8.9	12.1	1.08	1.24	1.00	1.14	NA**	1.45	1.18
Recalcitrant towards ozone degradation													
Oxazepam	12.3	11.3	7.1	13.5	18.4	9.7	1.64	1.75	1.37	1.66	1.34	1.16	1.49
Ketoprofen	13.4	12.7	5.5	13.2	23.9	9.7	1.78	1.97	1.06	1.62	1.74	1.16	1.56
Memantine	11.4	12.8	7.8	14.5	21.3	10.2	1.52	1.98	1.50	1.78	1.55	1.22	1.59
Ibuprofen	11.5	10.9	7.3	14.7	27	10.4	1.53	1.69	1.40	1.81	1.97	1.24	1.61
Beclomethasone	20	18	5.8	12	>>8.9	9.2	2.66	2.79	1.12	1.47	NA**	1.10	1.83
Atracurium	3.7	6.2	4.4	11	11.1	3.9	0.49	3.13	0.85	1.35	0.81	0.47	1.18
Flutamide	>>10.2	25	11.7	17.9	>>8.9	9.4	NA**	3.87	2.25	2.20	NA**	1.12	2.36
Fluconazole	15.1	18	10.7	20	>>8.9	22	2.01	2.79	2.06	2.46	NA**	2.63	2.39



Ozone dose for removal of the first decade of selected pharmaceuticals in each wastewater

Pharmaceutical	DDO ₃ (ppm O ₃)						DDO ₃ /DOC						Ave
	Eff1	Eff2	Eff3	Eff4	Eff5	Eff6	Eff1	Eff2	Eff3	Eff4	Eff5	Eff6	
<i>Easily degradable</i>													
Carbamazepine	5.1	5.4	2.2	4.3	10.8	3.5	0.68	0.84	0.42	0.53	0.79	0.42	0.61
Naproxen	5.7	5.0	2.5	6.4	10	3.7	0.76	0.77	0.48	0.79	0.73	0.44	0.66
Diclofenac	4.7	5.8	NA	3.5	10	NA	0.63	0.90	NA	0.43	0.73	NA	0.67
<i>Moderately degradable</i>													
Citalopram	5.0	7.8	2.0	7.1	15	5.0	0.67	1.21	0.38	0.87	1.09	0.60	0.80
Metoprolol	6.9	6.9	3.8	7.4	18.2	8.8	0.92	1.07	0.73	0.91	1.33	1.05	1.00
Fluoxetine	6.6	6.8	3.1	7.7	20	11.3	0.88	1.05	0.60	0.95	1.46	1.35	1.05
<i>Recalcitrant towards ozone degradation</i>													
Memantine	11.4	12.8	7.8	14.5	21.3	10.2	1.52	1.98	1.50	1.78	1.55	1.22	1.59
Ibuprofen	11.5	10.9	7.3	14.7	27	10.4	1.53	1.69	1.40	1.81	1.97	1.24	1.61
Beclomethasone	20	18	5.8	12	>>8.9	9.2	2.66	2.79	1.12	1.47	NA	1.10	1.83

Required ozone doses for removing pharmaceuticals from wastewater effluents.

Maria. G. Antoniou, Gerly Hey, Sergio Rodríguez-Vega, Aikaterini Spiliotopoulou Jerken Fick, Mats Tysklind, Jes la Cour Jansen, and Henrik R. Andersen

Science of the Total Environment, 456-457 (2013), 42-49.



UNIVERSITY OF THE AEGEAN



Global NEST

**13th INTERNATIONAL CONFERENCE
ON ENVIRONMENTAL SCIENCE AND TECHNOLOGY**

VOLUME OF ABSTRACTS

EDITOR: T.D. LEKKAS

**ATHENS, GREECE
5 – 7 SEPTEMBER 2013**

Global Network for Environmental Science and Technology
(Global-NEST)
University of the Aegean

Proceedings of the International Conference on Environmental Science and Technology

ISSN 1106-5516

Proceedings of the 13th International Conference on Environmental Science and Technology
5 – 7 September 2013, Athens, Greece

ISBN 978-960-7475-51-0

Editor: T.D. Lekkas

Editing co-ordinator: Christina Makri, Demetris F. Lekkas
Editing: Eleftheria Klontza, Dimitris Koutroumbis, Stavros Anastasiadis
Films – Montage - Printing: Diagramma